



HM 8-400KF Drum Wood Chipper

Œ







Technical Data and Equipment of the Wood Chipping Machine:

Infeed height: 400 mm Trunk diameter: 400 mm Infeed width: 708 mm Rotor shaft diameter: 80 mm Fly wheel mass: 470 kg

Drum diameter: 495 mm with quick exchangeable blades

Infeed: - conveyor belt; length 900 mm

> - top roller with steel teeth; diameter 600 mm - without any front end roller at the infeed table

- standard infeed table; length 900mm - length of the infeed table 1.500 mm

Augers: - 3 transversal augers

- discharge chute hydraulically foldable and height; Ejector:

ejecting height max. 4,50 m; depending on tyres

- discharge chute electrical rotatable

- discharge flap electrical adjustable

- automatic load-dependent infeed control with cycle mode Controls:

- two day counters and one overall operating hours counter

- infeed speed of top roller and conveyor belt infinitely variable

Claywood, Clattyland Lane, Beausale, Warwick, Warwickshire, CV35 7AF Tel:- 01926 484673

Email:- sales@fuelwood.co.uk

www.fuelwood.co.uk





- infeed direction reversible

- remote control with 10 m cable and control panel for all functions

- additional radio control

Colour: - silk matt green RAL 1028

- silk matt grey

Drive: via PTO shaft and V belt transmission

Drive rmp: max. 1.000 min-1

Drive performance: max. permissible 148 kW / 200 HP

Type of Wood Chipper		Article number
HEIZOHACK HM 8-400 K	Included	VB-04-000-00019
Equipment sieve HM 8-400 K:		
HM 8-400 / HM 8-400 K 50/50 mm with stop bars	Included	VB-04-016-00010
HM 8-400 / HM 8-400 K 60/80 mm with stop bars	Option	VA-04-016-00003
Equipment infeed table:		
Standard Infeed table	Included	VB-04-006-00007
Equipment yoke tractor side:		
Yoke 6 teeth 1 3/8" tractor side for type series SH	Included	VB-90-038-00003
Equipment yoke chipper side:		
Yoke with free wheel 6 teeth 1 3/4'' chipper side for type series SH (extra charge)	Included	VB-90-038-00008
Accessories chassis:		Article number
Chassis 40 km/h 500 mm trailing axle, spring-loaded pneumatic brake, supporting leg, drawbar, wings and lighting, nova grey silk matt MB 7350 Permissible total weight: 9000 kg Weight: approx.1000 kg Height of towing port: 500 mm	Included	VB-04-022-00007
Equipment chassis - tyres:		
Tyres 500/45 R22.5 up to 40 km/h, off-road tyres (unit price) only for chassis 40km/h, not for crane set-up at HM 8-500 K Vehicle width: chassis 40 km/h: approx. 2,80 m	Included	VB-04-022-00010
Equipment chassis - coupling point:		
Drawbar eye 50 mm, rotatable 290 mm length 200 x 200 bolted	Included	VB-90-039-00002
Accessories wood chipping machines / chassis:		Article number

Claywood, Clattyland Lane, Beausale, Warwick, Warwickshire, CV35 7AF Tel:- 01926 484673

Email:- sales@fuelwood.co.uk



Machinery Specialists



Radio control T60-2 **Functions:** - Raise/lower discharge chute - Right/left rotation of discharge chute - Raise/lower discharge flaps Included - In-feed forward/reverse VB-04-024-00002 ATTENTION: without speed adjustment of the pressure roller and conveyor belt

Consisting of:
Hand-held transmitter: MIDI System T60
Standard T60; 8 Relay outputs