

**FUELWOOD**

Forestry & Firewood  
Machinery Specialists

**Heizohack**

## HM 8-400KF Drum Wood Chipper

CE



### Technical Data and Equipment of the Wood Chipping Machine:

Infeed height:	400 mm
Trunk diameter:	400 mm
Infeed width:	708 mm
Rotor shaft diameter:	80 mm
Fly wheel mass:	470 kg
Drum diameter:	495 mm with quick exchangeable blades
Infeed:	<ul style="list-style-type: none"><li>- conveyor belt; length 900 mm</li><li>- top roller with steel teeth; diameter 600 mm</li><li>- <b>without</b> any front end roller at the infeed table</li><li>- standard infeed table; length 900mm</li><li>- length of the infeed table 1.500 mm</li></ul>
Augers:	<ul style="list-style-type: none"><li>- 3 transversal augers</li></ul>
Ejector:	<ul style="list-style-type: none"><li>- discharge chute hydraulically foldable and height; ejecting height max. 4,50 m; depending on tyres</li><li>- discharge chute electrical rotatable</li><li>- discharge flap electrical adjustable</li></ul>
Controls:	<ul style="list-style-type: none"><li>- automatic load-dependent infeed control with cycle mode</li><li>- two day counters and one overall operating hours counter</li><li>- infeed speed of top roller and conveyor belt infinitely variable</li></ul>

**Claywood, Clattyland Lane, Beusale, Warwick, Warwickshire, CV35 7AF**

**Tel:- 01926 484673**

**Email:- sales@fuelwood.co.uk**

**www.fuelwood.co.uk**

- infeed direction reversible
  - remote control with 10 m cable and control panel for all functions
  - **additional radio control**
  - silk matt green RAL 1028
  - silk matt grey
- Colour:
- Drive: via PTO shaft and V belt transmission
- Drive rpm: max. 1.000 min-1
- Drive performance: max. permissible 148 kW / 200 HP

Type of Wood Chipper			Article number
HEIZOHACK HM 8-400 K		Included	VB-04-000-00019
<b>Equipment sieve HM 8-400 K:</b>			
HM 8-400 / HM 8-400 K 50/50 mm with stop bars		Included	VB-04-016-00010
HM 8-400 / HM 8-400 K 60/80 mm with stop bars		Option	VA-04-016-00003
<b>Equipment infeed table:</b>			
Infeed table with additional chain conveyor		Included	VB-04-006-00008
<b>Equipment yoke tractor side:</b>			
Yoke 6 teeth 1 3/8" tractor side for type series SH		Included	VB-90-038-00003
<b>Equipment yoke chipper side:</b>			
Yoke with free wheel 6 teeth 1 3/4" chipper side for type series SH (extra charge)		Included	VB-90-038-00008
<b>Accessories chassis:</b>			<b>Article number</b>
Chassis 40 km/h 500 mm trailing axle, spring-loaded pneumatic brake, supporting leg, drawbar, wings and lighting, nova grey silk matt MB 7350  Permissible total weight: 9000 kg Weight: approx. 1000 kg Height of towing port: 500 mm		Included	VB-04-022-00007
<b>Equipment chassis - tyres:</b>			
Tyres 500/45 R22.5 up to 40 km/h, off-road tyres (unit price) only for chassis 40km/h, not for crane set-up at HM 8-500 K  Vehicle width: chassis 40 km/h: approx. 2,80 m		Included	VB-04-022-00010
<b>Equipment chassis - coupling point:</b>			
Drawbar eye 50 mm, rotatable 290 mm length 200 x 200 bolted		Included	VB-90-039-00002
<b>Accessories wood chipping machines / chassis:</b>			<b>Article number</b>

Claywood, Clattyland Lane, Beausale, Warwick, Warwickshire, CV35 7AF

Tel:- 01926 484673

Email:- sales@fuelwood.co.uk

**FUELWOOD**

**Forestry & Firewood  
Machinery Specialists**



<p><b>Radio control T60-2</b></p> <p><b>Functions:</b></p> <ul style="list-style-type: none"><li>- Raise/lower discharge chute</li><li>- Right/left rotation of discharge chute</li><li>- Raise/lower discharge flaps</li></ul> <p>- In-feed forward/reverse</p> <p><b>ATTENTION:</b> without speed adjustment of the pressure roller and conveyor belt</p> <p><b>Consisting of:</b> <b>Hand-held transmitter:</b> MIDI System T60 <b>Receiver:</b> Standard T60; 8 Relay outputs</p>	<p><b>Included</b></p>	<p>VB-04-024-00002</p>
---	------------------------	------------------------

Claywood, Clattyland Lane, Beausale, Warwick, Warwickshire, CV35 7AF

Tel:- 01926 484673

Email:- [sales@fuelwood.co.uk](mailto:sales@fuelwood.co.uk)

[www.fuelwood.co.uk](http://www.fuelwood.co.uk)