

# **FUELWOOD**

**Forestry & Firewood  
Machinery Specialists**

**Heizohack**

## **HM 10-500K Drum Wood Chipper**

**CE**



### **Technical Data of the Wood Chipping Machine:**

#### **HM 10-500 K**

Infeed height:	800 mm
Trunk diameter:	500 mm
Infeed width:	877 mm
Rotor shaft diameter:	80 mm
Fly wheel mass:	1.000 kg
Drum diameter:	495 mm
Rotor cover with sieve:	Included
Augers:	3
Ejecting height:	max. 4,66 m
Cutting system:	quick exchangeable blades
Infeed:	<ul style="list-style-type: none"><li>- conveyor belt; length 900 mm</li><li>- top roller with steel teeth; diameter 800 mm</li><li>- front end roller at the in-feed table</li><li>- <b>infeed table with conveyor belt; length 900 mm</b></li><li>- length of the infeed table 1.500 mm</li></ul>
Ejector: rotatable;	<ul style="list-style-type: none"><li>- discharge chute hydraulically foldable, adjustable for height and ejecting height</li><li>- discharge flap hydraulically adjustment</li></ul>
Controls:	<ul style="list-style-type: none"><li>- automatic load-dependent feed control with cycle mode</li><li>- two day counters and one overall operating hours counter</li></ul>

**Claywood, Clattyland Lane, Beusale, Warwick, Warwickshire, CV35 7AF**

**Tel:- 01926 484673**

**Email:- sales@fuelwood.co.uk**

**www.fuelwood.co.uk**

# FUELWOOD

Forestry & Firewood  
Machinery Specialists



- infeed speeds infinitely variable
- infeed direction reversible
- remote control with 10 m cable and control panel for all functions
- Radio control

Colour:

- satin gloss green RAL 6018
- satin gloss traffic grey RAL 7043

Drive:

via PTO shaft and V belt transmission

Drive rpm:

max. 1.000 min-1

Type of Wood Chipper			Article number			
HEIZOHACK HM 10-500 K		Included	VB-04-000-00016			
<b>Equipment sieve wood chipper HM 10-500 K:</b>						
HM 10-500 K 45/60 mm Hardox with stop bars (G30)		Included	VB-04-016-00026			
HM 10-500 K 60/80 mm Hardox with stop bars (G50)		Included	VB-04-016-00027			
HM 10-500 K 100/100 mm Hardox with stiffening		Option	VB-04-016-00028			
<b>Equipment rotor cover HM 10-500 K:</b>						
<b>Rotor cover HM 10-500 K for additional sieve</b> Consist of: - Rotor cover for sieve - 2 Hydraulic cylinder - Hand pump - Hydraulic hoses		Included	VB-04-003-00002			
<b>Equipment sieve - rotor cover HM 10-500 K:</b>						
HM 10-500 K 45/60 mm Hardox with stop bars (G30)		Included	VB-04-016-00034			
<b>Infeed table HM 10-500 K with conveyor belt</b> inclusive front end roller (extra charge)					Included	VB-04-006-00004
<b>Equipment counter knife HM 10-500 K:</b>						
<b>Counter knife HM 10-500 K multi-piece</b> - Carrier plate for the counter knife - Comb for carrier plate counter knife - Counter knife exchange plate (extra charge)		Included	VB-04-001-00004			
<b>Wear plate for blower housing Hardox standard</b> HM 500/800		Included	VA-04-508-00013			
<b>Wear plate discharge chute lower Hardox standard</b> HM 500/800		Included	VA-04-508-00015			
<b>Wear plate discharge chute upper Hardox standard</b> HM 500/800		Included	VA-04-508-00017			
<b>Wear plates discharge flaps Hardox standard</b> HM 500/800		Included	VA-04-508-00028			

Claywood, Clattyland Lane, Beusale, Warwick, Warwickshire, CV35 7AF

Tel:- 01926 484673

Email:- sales@fuelwood.co.uk

www.fuelwood.co.uk

# FUELWOOD

Forestry & Firewood  
Machinery Specialists



Equipment yoke tractor side:		
<b>Yoke 21 teeth 1 3/8"</b> tractor side for type series SH (extra charge)	<b>Included</b>	VB-90-038-00006
Equipment yoke chipper side:		
<b>Yoke with free wheel 6 teeth 1 3/4"</b> chipper side for type series SH (extra charge)	<b>Included</b>	VB-90-038-00008
Accessories chassis HM 10-500 K / HM 14-800 K:		Article number
<b>Chassis 40 km/h 500 mm</b> trailing axle, spring-loaded pneumatic brake, supporting leg, drawbar, wings and lighting, satin gloss Grey  Permissible total weight: 9000 kg Weight: approx. 1000 kg Height of towing port: <b>500 mm</b>	<b>Included</b>	VB-04-022-00007
Equipment chassis - tyres:		Article number
<b>Tyres 560/45 R22.5</b> up to 60 km/h, off-road tyres  <u>Vehicle width:</u> chassis 40 km/h: approx. 2,80 m	<b>Included</b>	VB-04-408-00052
Equipment chassis - coupling point:		
<b>Drawbar eye 50 mm, rotatable 290 mm length</b> 200 x 200 bolted (extra charge)	<b>Included</b>	VB-90-039-00002
Accessories wood chipping machines / chassis:		Article number
<b>Radio control T60-2</b>  <b>Functions:</b> - Raise/lower discharge chute - Right/left rotation of discharge chute - Raise/lower discharge flaps  - In-feed forward/reverse  <b>ATTENTION:</b> without speed adjustment of the pressure roller and conveyor belt  <b>Consisting of:</b> <b>Hand-held transmitter:</b> MIDI System T60 <b>Receiver:</b> Standard T60; 8 Relay outputs	<b>Included</b>	VB-04-024-00002

Claywood, Clattyland Lane, Beausale, Warwick, Warwickshire, CV35 7AF

Tel:- 01926 484673

Email:- [sales@fuelwood.co.uk](mailto:sales@fuelwood.co.uk)

[www.fuelwood.co.uk](http://www.fuelwood.co.uk)