

**Machinery Specialists** 



## HM 8-400KFL Drum Wood Chipper with Crane

Œ









## **Technical Data and Equipment** of the Wood Chipping Machine:

Infeed height: 400 mm Trunk diameter: 400 mm Infeed width: 708 mm 80 mm Rotor shaft diameter: Fly wheel mass: 470 kg

495 mm with quick exchangeable blades Drum diameter:

Infeed: - conveyor belt; length 900 mm

> - top roller with steel teeth; diameter 600 mm - without any front end roller at the infeed table

- infeed table with additional conveyor belt; length 900mm

- length oft the infeed table 1.500 mm

Augers: 3 transversal augers

Ejector: - discharge chute hydraulically foldable and height; ejecting height max. 4,50 m; depending on tyres

- discharge chute electrical rotatable

- discharge flap electrical adjustable

Controls: - automatic load-dependent infeed control with cycle mode

- two day counters and one overall operating hours counter

- infeed speed of top roller and conveyor belt infinitely variable

Claywood, Clattyland Lane, Beausale, Warwick, Warwickshire, CV35 7AF

Tel:- 01926 484673 Email:- sales@fuelwood.co.uk





- infeed direction reversible

- remote control with 10 m cable and control panel for all functions

- additional radio control

Colour: - silk matt green RAL 1028

- silk matt grey

Drive: via PTO shaft and V belt transmission

Drive rmp: max. 1.000 min-1

Drive performance: max. permissible 148 kW / 200 HP

**FTG-Mowi Timber crane** P30T with single telescopic extender 6.7m reach, 340kg lift at full reach. Full electric proportional control valve with Scanreco radio control Joysticks. Detachable 3-point A-frame with telescopic legs.

Type of Wood Chipper			Article number	
HEIZOHACK HM 8-400 K		Included	VB-04-000-00019	
Equipment sieve HM 8-400 K:				
HM 8-400 / HM 8-400 K 50/50 mm with stop bars		Included	VB-04-016-00010	
HM 8-400 / HM 8-400 K 60/80 mm with stop bars		Option	VA-04-016-00003	
	Equipment infeed table:			
Infeed table with HM 8-400 K conveyor belt		Included	VB-04-006-00008	
Equipment yoke tractor side:				
Yoke 6 teeth 1 3/8" tractor side for type series SH		Included	VB-90-038-00003	
	Equipment yoke chipper side:			
Yoke with free wheel 6 teeth 1 3/4´´ chipper side for type series SH (extra charge)		Included	VB-90-038-00008	
Acce	essories chassis:		Article number	
Chassis 40 km/h 500 mm trailing axle, spring-loaded pneumatic brake, supporting leg, drawbar, wings and lighting, nova grey silk matt MB 7350  Permissible total weight: 9000 kg Weight: approx.1000 kg Height of towing port: 500 mm		Included	VB-04-022-00007	
	Equipment chassis - tyres:			
Tyres 500/45 R22.5 up to 40 km/h, off-road tyres (unit price) only for chassis 40km/h, not for crane set-up at HM 8-500 K  Vehicle width: chassis 40 km/h: approx. 2,80 m		Included	VB-04-022-00010	
	Equipment chassis - coupling point:			
Drawbar eye 50 mm, rotatable 290 mm length 200 x 200 bolted		Included	VB-90-039-00002	

Claywood, Clattyland Lane, Beausale, Warwick, Warwickshire, CV35 7AF Tel:- 01926 484673

Email:- sales@fuelwood.co.uk





Radio control T60-2	
Nadio Control 100-2	
Functions: - Raise/lower discharge chute - Right/left rotation of discharge chute - Raise/lower discharge flaps - In-feed forward/reverse  Incl  ATTENTION: without speed adjustment of the pressure roller and conveyor belt  Consisting of: Hand-held transmitter: MIDI System T60 Receiver: Standard T60; 8 Relay outputs	ided VB-04-024-00002