

FUELWOOD

**Forestry & Firewood
Machinery Specialists**

Heizohack

HM 6-300 Second Hand (less than 70 hours) Drum Wood Chipper



Technical Data and Equipment of the Wood Chipping Machine:

Infeed height:	300 mm
Infeed width:	500 mm
Fly wheel mass:	130 kg
Drum diameter:	450 mm with quick exchangeable blades
Infeed:	<ul style="list-style-type: none">- conveyor belt; length 600 mm- top roller with steel teeth; diameter 380 mm- length of infeed table 900 mm
Augers:	2 transversal augers
Ejection height standard chute:	with chassis max. 3,42 m
Controls: optionally	<ul style="list-style-type: none">- automatic load-dependent infeed control with cycle mode- two day counters and one overall operating hours counter- infeed speed infinitely adjustable
Colour:	<ul style="list-style-type: none">- satin gloss Yellow- satin gloss Green
Drive:	via PTO shaft
Drive rpm:	max. 750 min-1

Claywood, Clattyland Lane, Beusale, Warwick, Warwickshire, CV35 7AF

Tel:- 01926 484673

Email:- sales@fuelwood.co.uk

www.fuelwood.co.uk

FUELWOOD

**Forestry & Firewood
Machinery Specialists**



Type of Wood Chipper		Article number
HEIZOHACK HM 6-300	Included	VB-04-000-00007
Sieve 35/40 mm	Included	VB-04-016-00013
Discharge chute manually rotatable HM 300/400	Included	VB-04-017-00001
Discharge flap manually adjustment HM 300/400	Included	VB-04-018-00002
Discharge chute manually foldable HM 400	Included	VB-04-018-00003
PTO Yoke Tractor side 6 spline 1 3/8" tractor side for type series SH	Included	VB-90-038-00003
Yoke with free wheel 6 teeth 1 3/4" chipper side for type series SH	Included	VB-90-038-00008
Chassis HM 300 25 km/h no parking brake a trailing axle, supporting leg, drawbar, mudguards and lighting, with tyres 10/75 - 15.3, satin gloss grey Height of towing port: 500 mm	Included	VB-04-022-00004
Trailer coupling ring 50 mm, rigid, HM 300/400 welded	Included	VE-90-039-00002

Claywood, Clattyland Lane, Beausale, Warwick, Warwickshire, CV35 7AF

Tel:- 01926 484673

Email:- sales@fuelwood.co.uk

www.fuelwood.co.uk